


Extended U Band x4 Active Multiplier 36-66GHz, Pout=+18dBm, Low Input Power

2023-5-5



Description:

AT-AM4-3666-18L is a full U band, active x4 frequency multiplier with low input power. The multiplier has an input frequency of 9-16.5 GHz with a typical output +18dBm from 36-66GHz.

The integrated input and output buffers deliver high output power at a low drive level. The multiplier also has a typical harmonic suppression. The input port is SMA female, and the output is WR-19. Other port configurations are available under different requirement.

More information, please visit www.atmicrowave.com

Feature

- ✓ Frequency: 36-66GHz
- ✓ Pout: +18dBm typical
- ✓ Input: 9-15GHz
- ✓ Low Harmonics

Application

- ✓ U band Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

Electronical Specifications:

Parameter	Min	Typical	Max
Input Frequency		9-16.5GHz	
Input Power	0dBm	+3dBm	+7dBm
Multiplier Factor		X4	
Output Frequency		36-66GHz	
Output Power	+16dBm	+18dBm	
X3/X5 Harmonic Suppression	-20	-35 dBc	
Drain Voltage		+5V/660mA	
Spec Temp		25C	





AT-AM4-3666-18L

Active Multiplier x4, 36-66GHz Pout=+18dBm

Mechanical Information

Item	Description
Input Port	SMA Female
Output Port	WR-19
Case Material	Copper
Finish	Gold Plated
Weight	190g
Size:	See outline


Absolute Maximum Ratings Table

Parameter	Value
Drain Supply	+8V
RF Input Power	+15dBm
Operating Temperature	0 to +50C
Storage Temperature	-45 to +125C

Notes:

- ✓ Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
- ✓ This data is only for reference, not for guaranteed specifications.
- ✓ Please contact AT Microwave team to make sure you have the most current data.
- ✓ Always pay attention to the temperature of the case, heatsink and fan are required if case temperature exceeds over 50C.






AT-AM4-3666-18L

Active Multiplier x4, 36-66GHz Pout=+18dBm

Test Data (25C)

Please note that test curves will vary slightly from unit to unit.



Pout vs Frequency, Pin=+3dBm



Dimension (Unit:mm)

