

2.4mm to 2.92 mm Adapter DC-40GHz

AT-AP-24X29X

Feature

- 2.4mm to 2.92mm Adapter
- Specified DC-40GHz
- Low Insertion Loss
- Excellent Broadband VSWR



Specifications -

Specifications guaranteed from -45 to +85°C, measured in a 50Ω system

Parameter	Frequency Range(GHz)	Min	Typ	Max	Unit
Insertion Loss	DC-26.5GHz		0.3		dB
	26.5-40GHz		0.5		dB
VSWR	DC-26.5GHz		1.15		
	26.5-40GHz		1.2		

Environmental

- 55 C to +125 C
- Corrosion: MIL-STD 202
- Vibration: MIL-STD 202

Materials

- Body: SU304 Polished & Passivated
- Center Contact: Beryllium Copper Gold Plated
- Insulators: PEI


Mechanical

- 1000 Cycle Min

Order Information

Connector #1	Connector #2	Part Number
2.4mm Female	2.92mm Female	AT-AP-24F29F
2.4mm Female	2.92mm Male	AT-AP-24F29M
2.4mm Male	2.92mm Female	AT-AP-24M29F
2.4mm Male	2.92mm Male	AT-AP-24M29M

Dimension



AT Microwave

RM1204,NO.2911,North Zhongshan RD, Putuo District , Shanghai ,China, 200063
 Tel:+8621-5291 8556 Email:sales@atmicrowave.com www.atmicrowave.com