

GPPO(Mini-SMP) to 2.4 mm Adapter

AT-AP-GPPOX24X

Feature

- GPPO(Mini-SMP) to 2.4 Adapter
- Specified DC-50GHz
- Low Insertion Loss
- Excellent Broadband VSWR



Specifications -

Specifications guaranteed from -45 to +85°C, measured in a 50Ω system

Parameter	Frequency Range(GHz)	Min	Typ	Max	Unit
Insertion Loss	DC-40GHz		0.8		dB
	40-50GHz		1		dB
VSWR	DC-40GHz		1.2		
	40-50GHz		1.25		

Environmental

- 55 C to +125 C
- Corrosion: MIL-STD 202
- Vibration: MIL-STD 202

Materials

- Body: SU304 Polished & Passivated
- Center Contact: Beryllium Copper Gold Plated
- Insulators: PEI


Mechanical

1000 Cycle Min

Order Information

Connector #1	Connector #2	Part Number
GPPO Female	2.4mm Female	AT-AP-GPPOF24F
GPPO Female	2.4mm Male	AT-AP-GPPOF24M
GPPO Male	2.4mm Female	AT-AP-GPPOM24F
GPPO Male	2.4mm Male	AT-AP-GPPOM24M

Dimension



AT Microwave

RM1204,NO.2911,North Zhongshan RD, Putuo District , Shanghai ,China, 200063
Tel:+8621-5291 8556 Email:sales@atmicrowave.com www.atmicrowave.com