

GPPO(Mini-SMP) to 2.92mm Adapter

AT-AP-GPPOX29X

Feature

GPPO(Mini-SMP) to 2.92mm Adapter

Specified DC-40GHz

Low Insertion Loss

Excellent Broadband VSWR



Specifications -

Specifications guaranteed from -45 to +85°C, measured in a 50Ω system

Parameter	Frequency Range(GHz)	Min	Typ	Max	Unit
Insertion Loss	DC-26.5GHz		0.8		dB
	26.5-40GHz		1		dB
VSWR	DC-26.5GHz		1.2		
	26.5-40GHz		1.25		

Environmental

-55 C to +125 C

Corrosion: MIL-STD 202

Vibration: MIL-STD 202

Materials

Body: SU304 Polished & Passivated

Center Contact: Beryllium Copper Gold Plated

Insulators: PEI


Mechanical

1000 Cycle Min

Order Information

Connector #1	Connector #2	Part Number
GPPO Female	2.92mm Female	AT-AP-GPPOF29F
GPPO Female	2.92mm Male	AT-AP-GPPOF29M
GPPO Male	2.92mm Female	AT-AP-GPPOM29F
GPPO Male	2.92mm Male	AT-AP-GPPOM29M

Dimension



AT Microwave

RM1204,NO.2911,North Zhongshan RD, Putuo District , Shanghai ,China, 200063

Tel:+8621-5291 8556 Email:sales@atmicrowave.com www.atmicrowave.com