

AT-BTBB-0043-3520

10MHz-43GHz Bench-Top Broadband Amplifier

10MHz-43GHz Bench-Top Broadband Amplifier

2024-11-1



Product Overview

AT-BTBB-0043-3520 is bench-top broadband amplifier from 10MHz-43GHz, with $P_{out}=+20\text{dBm}$, $NF=6\text{dB}$.

It can be used both as Power amplifier or low noise amplifier. The bench-top amplifier is with 220V power supply for easy using.

More information, please visit www.atmicrowave.com

Advantages

- ✓ Frequency: 10MHz-43GHz
- ✓ $P_{sat}:+22\text{dBm}$
- ✓ Small signal gain: 35dB
- ✓ Bench-Top Test

Application

- ✓ 5G Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

Key Features

Parameter	Min	Typical	Max
Frequency		10MHz-43GHz	
Gain	33dB	35dB	
P1dB	+18dBm +16dBm	10MHz-33GHz: +20dBm 33-43GHz: +18dBm	
Psat	+20dBm +17dBm	10MHz-33GHz: +22dBm 33-43GHz: +20dBm	
Drain Supply	+90V	+220V	+240V
Power Consumption		40W	
NF(1-40GHz)		6dB	
Input Return Loss	-5	-10 dB	
Output Return Loss	-5	-10 dB	
Spec Temp		25C	

Shanghai AT Microwave Limited

Tel:021-6229 1233

Email:sales@atmicrowave.com

www.atmicrowave.com





AT-BTBB-0043-3520

10MHz-43GHz Bench-Top Broadband Amplifier

Mechanical Information

Item	Description
Input Port	2.92mm Female
Output Port	2.92mm Female
Case Material	Aluminum
Finish	Painting
Weight	1.6KG
Size:	See Outline


Absolute Maximum Ratings Table

Parameter	Value
Drain Supply	+260V
RF Input Power	+15 dBm
Operating Temperature	0 to +50C
Storage Temperature	-45 to +125C

Notes:

1. Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
2. This data is only for reference, not for guaranteed specifications.
3. Please contact AT Microwave team to make sure you have the most current data.





AT-BTBB-0043-3520

10MHz-43GHz Bench-Top Broadband Amplifier

Bench-Top Dimension (unit in mm)

