



AT-BTHPA-2430-3634N

24-30GHz High Power Amplifier

24-30GHz High Power Amplifier

2022-12-1

Gain=36dB, Pout=+34dBm,



Product Overview

AT-BTHPA-2430-3634N is GaAs Based high gain power amplifier with +35dBm output power in the frequency of 24-30GHz. The module is with 2.92mm connector.

The power amplifier has high gain, high linearity, low input/output return loss and flat gain response.

More information, please visit www.atmicrowave.com

Advantages

- ✓ Frequency: 24-30GHz
- ✓ Psat:+34dBm
- ✓ Small signal gain: 36dB
- ✓ Single Power Supply

Application

- ✓ 5G Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

Key Features

Parameter	Min	Typical	Max
Frequency		24-30GHz	
Gain	33dB	36dB	
P1dB		+32dBm	
Psat	+32dBm	+34dBm	
Input Return Loss		-12dB	
Output Return Loss		-8dB	
Power Supply	+90V	+220V	+240V
Power Consumption		50W	
Spec Temp		24C	





AT-BTHPA-2430-3634N

24-30GHz High Power Amplifier

Mechanical Information

Item	Description
Input Port	2.92mm Female
Output Port	2.92mm Female
Case Material	Aluminum
Finish	Painting
Weight	3.5KG
Size:	See outline


Absolute Maximum Ratings Table

Parameter	Value
Drain Supply	+260V
RF Input Power	+10 dBm
Operating Temperature	-40 to +70C
Storage Temperature	-45 to +85C

Notes:

1. Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
2. This data is only for reference, not for guaranteed specifications.
3. Please contact AT Microwave team to make sure you have the most current data.





AT-BTHPA-2430-3634N

24-30GHz High Power Amplifier

Dimension: (unit in mm)

