

4Ways Wilkinson Power Divider/Combiner

AT-PD4-0126

REV A

Feature

- 1-26.5 GHz Broadband
- Low Insertion Loss
- Outstanding Phase and Amplitude Balance

Electrical Specifications -

Specifications guaranteed from -45 to +85°C, measured in a 50Ω system

Parameter	Frequency Range(GHz)	Min	Typ	Max	Unit	
Normal Power Splitting	1-26.5GHz		6		dB	
Normal Phase Shift			0		Degree	
Amplitude Balance			+/-0.5		dB	
Phase Balance			+/- 6		Degree	
Insertion Loss				3.2		dB
VSWR				1.6		
Isolation				16		dB
CW Peak				20		W
Peak Power				3000		W
Weight				260		g
Dimension(L/W/H)			110.5x73.7x12.7			mm


Order Information

Part Number	Description
AT-PD4-0126	4Ways 1-26.5GHz Power Divider With SMA Female Connectors

Consult factory for other connectors option

Dimension

Unit: mm/Degree



AT Microwave

RM1204,NO.2911,North Zhongshan RD, Putuo District , Shanghai ,China, 200063

Tel:+8621-5291 8556 Email:sales@atmicrowave.com www.atmicrowave.com

4Ways Wilkinson Power Divider/Combiner

AT-PD4-0126

Typical Performance




Figure 1: Input Port VSWR




Figure 2: Output Port VSWR




Figure 3: Insertion Loss




Figure 4: Output Port Isolation




Figure 5: Output Port Amplitude Balance




Figure 6: Output Phase Balance

AT Microwave reserves the right to make changes to the information contained herein without notice.

AT Microwave

RM1204,NO.2911, North Zhongshan RD, Putuo District, Shanghai, China, 200063

Tel: +8621-5291 8556 Email: sales@atmicrowave.com www.atmicrowave.com