

Rugged Straight Waveguide, 1.25inch 170-260GHz, WR-04

2023-5-5



Product Overview

AT Microwave provides rugged straight waveguide with high performance. RSW series Flanges are anti-cocking design for high precision test application.

AT Microwave offers straight waveguide covering 33-325GHz, with waveguide port from WR-22 to WR-03.

More information, please visit www.atmicrowave.com

Advantages

- ✓ Rugged Application
- ✓ Low Insertion Loss
- ✓ Anti-cocking Design
- ✓ Low Cost, Fast Delivery

Application

- ✓ Labs Test
- ✓ Radar System
- ✓ High Performance Application

Key Features

Parameter	Min	Typical	Max
Passband Frequency	170GHz		260GHz
VSWR		1.15	
Length (note)		1.25inch	


Note: Length can be customized according to request.



Mechanical Information

Item	Description
Input Port	WR-04, UG-387/U-M Flange with anti-cocking Flange
Output Port	WR-04, UG-387/U-M Flange with anti-cocking Flange
Case Material	Copper
Finish	Gold Plated
Weight	35g

Dimension (unit mm)



Dimensions(mm)		
Waveguide	-A-	-B-
WR-15	3.76	1.88
WR-12	3.10	1.55
WR-10	2.54	1.27
WR-08	2.03	1.02
WR-06	1.65	0.83
WR-05	1.30	0.65
WR-04	1.09	0.55
WR-03	0.86	0.43

